DPM 5544



MATERIAL SAFETY DATA SHEET

261

JAN 1 5 1980

(Approved by U.S. Department of Labor as "essentially similar" to Form LSB-00S-4)

| SECTION IDENTIFICATION OF PRODUCT | | | | | | |
|-------------------------------------|-------------------------|----------------------|-----------------------------------|--|--|--|
| MANUFACTURER'S NAME | AMERICAN CYANAMID COM | (201) 835-3100 | | | | |
| ADDRESS | Wayne, New Jersey 07470 | | | | | |
| TRADE NAME AND SYNONYMS | Diethylaniline | | | | | |
| CHEMICAL NAME AND SYNONYMS | N,N-Diethylaniline | | | | | |
| CHEMICAL FAMILY | Aromatic amine | MOLECULAR FORMULA | C ₁₀ H ₁₅ N | | | |

| SECTION II HAZARDOUS COMPONENTS OF MIXTURES | | | | | |
|---|----------------|---|-------------------------------|--|--|
| | COMPONENT | % | THRESHOLD LIMIT VALUE (UNITS) | | |
| • . | Not applicable | | | | |
| | | | | | |
| | | | | | |

| SECTION III PHYSICAL DATA | | | | | |
|--|--|---------------------------------------|-----------------|--|--|
| APPEARANCE AND ODOR | Clear, Straw-Corolled right which darkens on standing, | | | | |
| BOILING POINT (DEGREES 420.8 FAHRENHEIT) | | SPECIFIC GRAVITY (WATER = 1) | 0.939 at 15.5 C | | |
| VAPOR PRESSURE (MM. OF MERCURY) | Not available | PERCENT VOLATILE (BY VOLUME) | Negligible | | |
| VAPOR DENSITY (AIR = 1) | 5.0 | EVAPORATION RATE (BUTYL ACETATE = 1) | Less than 1 | | |
| SOLUBILITY IN WATER | Moderate | EVAPORATION RATE (ETHYL ETHER = 1) | Less than 1 | | |

| FLASH POINT (SPECIFY METHOD) (DEGREES FAHRENH | 185 Closed Cup | FLAMMABLE LIMITS (PERCENT BY VOLUME) | LOWER UPPER Not available |
|---|---|--|--|
| FIRE-EXTINGUISHIN MEDIA | GFoam, CO ₂ , dry chemical, c | or water spray | • |
| SPECIAL FIRE-FIGHTING PROCEDURES | Firemen should wear self-c clothing. Fight fire from Use water-spray to keep co | contained breathing apparatus upwind. After fire, shower ontainers cool. | and full protective and change clothing. |
| UNUSUAL FIRE AND EXPLOSION HAZARDS | None | | |

THIS INFORMATION IS GIVEN WITHOUT A WARRANTY OR REPRESENTATION. WE'DO NOT ASSUME ANY LEGAL RESPONSIBILITY FOR SAME, NOR DO WE GIVE PERMISSION, INDUCEMENT, OR RECOMMENDATION TO PRACTICE ANY PATENTED INVENTION WITHOUT A LICENSE. IT IS OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION. BEFORE USING ANY PRODUCT READ ITS LABEL.

READ THE BACK

| SECTION V HEALTH HAZARD DATA | | | | |
|--|---|--|--|--|
| THRESHOLD LIMIT VALUE | No TLV has been established | | | |
| EFFECTS OF OVEREXPOSURE | Dizziness, headache and bluish discoloration ("cyanosis") of lips, ear lobes and fingernail beds. | | | |
| EMERGENCY AND FIRST AID PROCEDURES | Remove to fresh air and call a physician at once. In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes. If cyanosis is present, shower with soap and warm water, with special attention to scalp and fingernails. Administer oxygen until physician arrives. | | | |

| SECTION VI REACTIVITY DATA | | | | | |
|---|---------------------------------------|---|------------------------|--|--|
| | UNSTABLE | | CONDITIONS TO AVOID | | |
| STABLE | | Х | None | | |
| INCOMPATIBILITY (Materials to avoid) | | | | | |
| HAZARDOUS Thermal decomposition may produce carbon monoxide DECOMPOSITION and/or carbon dioxide PRODUCTS Thermal decomposition may produce carbon monoxide | | | | | |
| HAZARDOUS | I I I I I I I I I I I I I I I I I I I | | | | |
| POLYMERIZATION | WILL NOT OCCUR | Х | None | | |

| SECTION VII SPILL OR LEAK PROCEDURES | | | | |
|---|--|--|--|--|
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED | Wear appropriate protective equipment and clothing. Cover with some inert absorbent material; sweep up and place in a waste disposal container. Flush area with water. | | | |
| WASTE DISPOSAL METHOD | Disposal must be made in accordance with federal, state and local regulations. | | | |

| SECTION VIII SPECIAL PROTECTION INFORMATION | | | | | |
|---|-------------------------|--|---------------|-----------------|--|
| RESPIRATORY PROTECTION (Specify type) | evaluation. | respiratory protect If protection is re to the degree of exp | equired, use | be det respi | ermined by an industrial hygiene ratory protection approved by NIOSH |
| | LOCAL EXHAUST | SPECIAL None | | | |
| VENTILATION | MECHANICAL (General) | Acceptable | | OTHER | None |
| PROTECTIVE GLOVES | Rubber | | EYE PROTEC | TION | Splashproof goggles |
| OTHER PROTECTIVE EQUIPMENT | Eyewash | fountain and safety | shower | | |

| SECTION IX SPECIAL PRECAUTIONS | | | | |
|--|--|--|--|--|
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING | Precautions for a Class III A combustible liquid | | | |
| OTHER PRECAUTIONS | None | | | |

| | SECTION X DATE AND SOURCE OF INFORMATION | |
|-----------------------------------|--|------------------|
| DATE Revised November 30, 1976 | NAME AND TITLE C. Boyd Shaffer, Ph.D. Director of Toxicology | SHEET NUMBER 261 |